




Super HC



ONOME MAIS CONFIÁVEL DO MUNDO
EMCORREIAS E MANGUEIRAS



Circunferência Externa		Perfil 3V
(pol)	(mm)	
25,0	635	3V250
26,5	675	3V265
28,0	710	3V280
30,0	760	3V300
31,5	800	3V315
33,5	850	3V335
35,5	900	3V355
37,5	955	3V375
40,0	1015	3V400
42,5	1080	3V425
45,0	1145	3V450
47,5	1205	3V475
50,0	1270	3V500
53,0	1345	3V530
56,0	1420	3V560
60,0	1525	3V600
63,0	1600	3V630
67,0	1700	3V670
71,0	1805	3V710
75,0	1905	3V750
80,0	2030	3V800
85,0	2160	3V850
90,0	2285	3V900
95,0	2415	3V950
100,0	2540	3V1000
106,0	2690	3V1060
112,0	2845	3V1120
118,0	2995	3V1180
125,0	3175	3V1250
132,0	3355	3V1320
140,0	3555	3V1400

Circunferência Externa		Perfil 5V
(pol)	(mm)	
50,0	1270	5V500
53,0	1345	5V530
56,0	1420	5V560
60,0	1525	5V600
63,0	1600	5V630
67,0	1700	5V670
71,0	1805	5V710
75,0	1905	5V750
80,0	2030	5V800
85,0	2160	5V850
90,0	2285	5V900
95,0	2415	5V950
100,0	2540	5V1000
106,0	2690	5V1060
112,0	2845	5V1120
118,0	2995	5V1180
125,0	3175	5V1250
132,0	3355	5V1320
140,0	3555	5V1400
150	3810	5V1500
160	4065	5V1600
170	4320	5V1700
180	4570	5V1800
190	4825	5V1900
200	5080	5V2000
212	5385	5V2120
224	5690	5V2240
236	5995	5V2360
250	6350	5V2500
265	6730	5V2650
280	7110	5V2800
300	7620	5V3000
315	8000	5V3150
335	8510	5V3350
355	9017	5V3550

Circunferência Externa		Perfil 8V
(pol)	(mm)	
100,0	2540	8V1000
106,0	2690	8V1060
112,0	2845	8V1120
118,0	2995	8V1180
125,0	3175	8V1250
132,0	3355	8V1320
140,0	3555	8V1400
150,0	3810	8V1500
160,0	4065	8V1600
170,0	4320	8V1700
180,0	4570	8V1800
190,0	4825	8V1900
200,0	5080	8V2000
212,0	5385	8V2120
224,0	5690	8V2240
236,0	5995	8V2360
250,0	6350	8V2500
265,0	6730	8V2650
280,0	7110	8V2800
300,0	7620	8V3000
315,0	8000	8V3150
335,0	8510	8V3350
355,0	9017	8V3550
375,0	9525	8V3750
400,0	10160	8V4000
425,0	10795	8V4250
450,0	11430	8V4500
475,0	12065	8V4750
500,0	12700	8V5000
560,0	14225	8V5600

Nota: Os desenhos acima não estão em escala.